

SolarEdge Energy Bank 10kWh Battery For North America

HOME BACKUP



Optimized for SolarEdge Energy Hub Inverters⁽¹⁾

- Maximized system performance, gaining more energy to store and use for on-grid and backup power applications
- Integrates with the complete SolarEdge residential offering, providing a single point of contact for warranty, support, training, and simplified logistics & operations
- DC coupled battery featuring superior overall system efficiency, from PV to battery to grid
- Scalable solution for increased power and capacity with multiple SolarEdge inverters and batteries
- Solar, storage, EV charging, and smart devices all monitored and managed by a single app to optimize solar production, consumption and backup* power
- Wireless communication to the inverter, reducing wiring, labor and installation faults
- Simple plug and play installation, with automatic SetApp-based configuration
- Includes multiple safety features for battery protection

* Backup application are subject to local regulation and may require additional components and firmware upgrade

/ SolarEdge Energy Bank

10kWh Battery

For North America

BAT-10K1P⁽²⁾

BATTERY SPECIFICATION

| | | |
|---|------------------------|-------|
| Usable Energy (100% depth of discharge) | 9700 | Wh |
| Continuous Output Power | 5000 | W |
| Peak Output Power (for 10 seconds) | 7500 | W |
| Peak Roundtrip Efficiency | >94.5 | % |
| Warranty ⁽³⁾ | 10 | Years |
| Voltage Range | 350-450 | Vdc |
| Communication Interfaces | Wireless* | |
| Batteries per Inverter | Up to 3 ⁽⁴⁾ | |

STANDARD COMPLIANCE

| | | |
|-----------|--------------------------------|--|
| Safety | UL1642, UL1973, UL9540, UN38.3 | |
| Emissions | FCC Part 15 Class B | |

MECHANICAL SPECIFICATIONS

| | | |
|--|---|---------|
| Dimensions (W x H x D) | 31.1 x 46.4 x 9.84 / 790 x 1179 x 250 | in / mm |
| Weight | 267 / 121 | lb / kg |
| Mounting ⁽⁵⁾ | Floor or wall mount ⁽⁶⁾ | |
| Operating Temperature ⁽⁷⁾ | +14 to +122 / -10 to +50 | °F / °C |
| Storage Temperature (more than 3 months) | +14 to +86 / -10 to +30 | °F / °C |
| Storage Temperature (less than 3 months) | -22 to +140 / -30 to +60 | °F / °C |
| Altitude | 6562 / 2000 | ft / m |
| Enclosure Protection | IP55 / NEMA 3R - indoor and outdoor (water and dust protection) | |
| Cooling | Natural convection | |
| Noise (at 1m distance) | <25 | dBa |

* The SolarEdge Energy Bank is designed for use with SolarEdge Energy Net for wireless communication. The inverter might require a matching SolarEdge Energy Net Plug-in (more details below).

Using RS485 could reduce the usable energy to 9500Wh.

(1) Please refer to the SolarEdge Energy Bank battery connections and configuration application note for compatible inverters.

(2) These specifications apply to part number BAT-10K1PS0B-01.

(3) For warranty details please refer to the SolarEdge Energy Bank battery Limited Warranty.

(4) Installations with multiple SolarEdge Energy Bank batteries connected to a single inverter require a pair of branch connectors (DC + and DC -) per battery excluding the last battery. Support for 3 batteries is pending supporting inverter firmware. The branch connectors should be purchased separately.

(5) Installation and mounting requires handles that should be purchased separately. Please refer to the Accessories' PN table below.

(6) The floor stand is purchased separately. One floor stand is required per SolarEdge Energy Bank battery. Please refer to the Accessories' PN table below.

(7) Please note that operating the SolarEdge Energy Bank at extreme temperatures for extended durations of time may void the Energy Bank's warranty coverage.

Please see the Energy Bank Limited Product Warranty for additional details.

SolarEdge Energy Bank Battery – Accessories (purchased separately)

| Accessory | PN |
|--|--------------------|
| Floor stand | IAC-RBAT-FLRSTD-01 |
| Branch connectors set (includes a pair of DC + and DC - connectors) Required for installations with multiple SolarEdge Energy Bank batteries with a single inverter | IAC-RBAT-USYCBL-01 |
| Handles | IAC-RBAT-HANDLE-01 |
| SolarEdge Energy Net Plug-in | ENET-HBNP-01 |
| Battery inverter extension cable 2m long (MC4 to terminal block) | IAC-RBAT-10M420-01 |